

F-PODIUM CARBON R, CARBON/MARLIN BLUE, 2022

obj. č: 010.22048



Sugerowana cena

37.959 zł

Specyfikacje techniczne

produkowane rozmiary

S: 390mm / M: 420mm / L: 470mm / XL: 510mm

rama

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

widelec

Fox 34 Step Cast Float FIT4 Evol Factory Kashima, 110mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, compression micro-adjustment at low-speed, rebound, air preload

stery

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

przerzutka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger GX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty

Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore

mostek

MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sztyca

Onoff Helium Carbon 0-R, diameter 31.6mm, length 400mm

siodełko

Fizik Antares R7

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

łańcuch

Sram GX Eagle, 12s, Powerlock

kaseta

Sram XG-1275, 10-50T, 12s

szprychy

Mavic straightpull double butted, contactless lacing

rafki

Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes

obudowa

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

zamówienie numer

010.22048

gripy

Onoff Diamond, 1lock-on, 135mm

amortyzator Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	regulacja amortyzatora Firm compression, light rebound, air volume spacer 0.2
korba 34T, CNC-machined alloy, X-SYNC 2	mocowanie przerzutki Sram UDH

Galeria

