

PODIUM CARBON R 29, TRANSLUCENT BLUE CARBON/MARLIN BLUE, 2022

obj. č: 010.22036



Sugerowana cena

29.639 zł

Specyfikacje techniczne

produkowane rozmiary

S: 390mm / M: 420mm / L: 470mm / XL: 510mm

rama

Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,

widelec

Fox 32 Step Cast Float FIT4 EVOL Factory Kashima, 100mm, tapered steerer tube, 15x110mm Boost axle, remote lockout, offset 44mm. Settings: lockout, compression micro-adjustment at low-speed, rebound, air preload

stery

Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°

przerzutka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:2

manetki

Sram Trigger GX Eagle, 12s, X-Actuation 1:2

klamki hamulca

Sram Level TLM, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty

Truvativ Stylo Carbon Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore

mostek

MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm

szttyca

Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm

siodełko

Fizik Antares R7

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram XG-1275, 10-50T, 12s

szprychy

Mavic straightpull double butted, contactless lacing

rafki

Mavic Crossmax Carbon SL R 29, 26mm internal width, hookless, tubeless ready, 24 spokes

obudowa

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

zamówienie numer

010.22036

gripy

Onoff Diamond, 1lock-on, 135mm

przedni hamulec Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
korba 34T, steel, X-Sync 2	mocowanie przerzutki Sram UDH

Galeria

