

F-PODIUM CARBON DC, CARBON/CHERRY RED, 2022

obj. č: 010.22052

Sugerowana cena

27.039 zł



Specyfikacje techniczne

produkowane rozmiary S: 390mm / M: 420mm / L: 470mm / XL: 510mm	waga 12,4 Kg
rama F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.	widelec Rockshox SID Select RL 29, 120mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload
stery Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom	przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
uchwyty Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore	mostek MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm
sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M/L/XL size 387x125mm	siodełko Fizik Antares R7
piasta przednia Mavic, Boost 15x110mm, IS 6 bolts	tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
łańcuch Sram SX Eagle, 12s, Powerlock	kaseta Sram XG-1230, 11-50T, 12s
szprychy Mavic straightpull duble butted, contactless lacing	rafki Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes
obudowa Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead	zamówienie numer 010.22052
gripy Onoff Twin, 1lock-on, 135mm	amortyzator Rockshox SID Select+ RLR Debonair, 185x50mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

przedni hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
regulacja amortyzatora Light compression, medium rebound, Lockout 430, 1 Token	korba 34T, steel, X-Sync 2
mocowanie przerzutki Sram UDH	

Galeria

