

FOXY CARBON XR MIND, RACING SILVER/YELLOW, 2023

obj. č: 010.23121

Sugerowana cena

52.499 zł



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rama Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Geometry kit included. MIND System (EU only)
widelec Öhlins RXF 36 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber. Fork settings: C20 R40	stery "Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"
przerzutka Sram X01 Eagle AXS, roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Eagle AXS Rocker paddle, 12s
klamki hamulca Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust	uchwyty Sram X01 Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
mostek Onoff Krypton FG 30mm, CNC, 31.8mm barbore	sztycja Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
siodełko SDG BEL-AIR 3.0, LPU foam, steel rails	piasta przednia e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
tylna piasta e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub	łańcuch Sram GX Eagle, 12s, Powerlock
kaseta Sram XG-1295, 10-52T, 12s	szprychy e*thirteen custom Hive triple-buttressed black steel, alloy nipples, nipple washers
rafki e*thirteen Race Carbon Enduro IW30, Hookless carbon rim, 30mm internal width, tubeless ready, 28 spokes	obudowa Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead
zamówienie numer 010.23121	gripy Onoff Desert, 1lock-on, 135mm

amortyzator
Öhlins TTX Air 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

tylny hamulec
Sram Code RSC, oversized 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

korba
32T, CNC-machined alloy, X-SYNC 2

inne
*Geometry kit included: steering cups: +/- 1°

przedni hamulec
Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

regulacja amortyzatora
C10 compression, R35 rebound. Volume reducers 16.000 (2xF+1E)

mocowanie przerzutki
Sram UDH

Galeria

