

CRAFTY CARBON RR MIND, CARBON/CHERRY RED, 2022

obj. č: 010.22244



Sugerowana cena

54.599 zł

Specyfikacje techniczne

produkowane rozmiary

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

rama

Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

widelec

Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload

stery

"Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"

przerzutka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca

Sram G2 RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust

uchwyty

Race Face Aeffect ebike, 165mm

kierownica

Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

mostek

Onoff Krypton FG 30mm, CNC, 31.8mm barbare

sztyca

Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm

siodełko

FIZIK Terra Aidon X5 145mm

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

łańcuch

Sram NX Eagle, 12s, Powerlock

kaseta

Sram XG-1275, 10-52T, 12s

szprychy

Mavic straightpull duble butted, contactless lacing

rafki

Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes

obudowa

Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead,

zamówienie numer

010.22244

gripy

Onoff Diamond, 1lock-on, 135mm

amortyzator

Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

przedni hamulec Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	tylny hamulec Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
regulacja amortyzatora medium compression, medium rebound, air volume spacer 0.2	korba Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
mocowanie przerzutki Mondraker M068	silnik + akumulator Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300

Galeria

