

PRIME 29, BLACK/RACING SILVER, 2022

obj. č: 010.22174



Specyfikacje techniczne

produkowane rozmiary XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm	waga 22,2 Kg
rama Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery with integrated alloy cover, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor	widelec RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click	klamki hamulca Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
uchwyty Race Face Aeffect ebike, 165mm	kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore	szttyca Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm
siodełko FIZIK Terra Aidon X5 145mm	piasta przednia Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
tylna piasta Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram PG-1210, 11-50T, 12s	szprychy CN round stainless steel
rafki MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes	obudowa Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
zamówienie numer 010.22174	gripy Onoff Diamond, 1lock-on, 135mm
przedni hamulec Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
korba Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD	mocowanie przerzutki Mondraker M068

silnik + akumulator

Bosch Performance Line CX Cruise (25Km/h) GEN4, Bosch

Powertube 625Wh, Bosch Purion

Galeria

