

# CHRONO CARBON RR 29, CARBON/BLACK/RACING SILVER, 2022

obj. č: 010.22028



Sugerowana cena

**17.419 zł**

## Specyfikacje techniczne

|                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>S: 395mm / M: 430mm / L: 470mm / XL: 520mm                                                                                                                                                                                          | <b>rama</b><br>Chrono 29 Stealth full Carbon, XC Forward Geometry, 73mm BSA bottom bracket, tapered steerer tube, HHG Internal Cable routing, Boost 12x148mm rear axle, Comfort Flat chainstays (Flatstays) design |
| <b>widelec</b><br>Rockshox SID SL Ultimate RL 29, 100mm, Charger Race day, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload | <b>stery</b><br>Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°                                                                         |
| <b>przerzutka</b><br>Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                                                                                | <b>manetki</b><br>Sram Trigger NX Eagle, 12s, X-Actuation 1:1                                                                                                                                                      |
| <b>klamki hamulca</b><br>Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings                                                                                                                                                            | <b>uchwyty</b><br>Sram GX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm                                                                                                       |
| <b>support</b><br>Sram DUB BSA, sealed bearings, 73mm                                                                                                                                                                                                              | <b>kierownica</b><br>Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare                                                                               |
| <b>mostek</b><br>MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: size S: 60mm, size M: 70mm, size L: 80mm, size XL: 90mm                                                                                                                                  | <b>sztyca</b><br>Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm                                                                                                                         |
| <b>siodełko</b><br>Mondraker XC Series, steel rail                                                                                                                                                                                                                 | <b>piasta przednia</b><br>Mavic, Boost 15x110mm, IS 6 bolts                                                                                                                                                        |
| <b>tylna piasta</b><br>Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts                                                                                                                                                                                     | <b>łańcuch</b><br>Sram SX Eagle, 12s, Powerlock                                                                                                                                                                    |
| <b>kaseta</b><br>Sram PG-1230, 11-50T, 12s                                                                                                                                                                                                                         | <b>szprychy</b><br>Mavic straightpull duple butted, contactless lacing                                                                                                                                             |
| <b>rafki</b><br>Mavic Crossmax SL S 29, 25mm internal width, Maxtal welded rim, hookless, tubeless, 24 spokes                                                                                                                                                      | <b>obudowa</b><br>Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead, Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead                               |
| <b>zamówienie numer</b><br>010.22028                                                                                                                                                                                                                               | <b>gripy</b><br>Onoff Diamond, 1lock-on, 135mm                                                                                                                                                                     |
| <b>przedni hamulec</b><br>Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                                                                     | <b>tylny hamulec</b><br>Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                       |

**korba**

34T, CNC-machined alloy, X-SYNC 2

**mocowanie przerzutki**

Mondraker M068

**Galeria**

---

