

CHRONO 29, BLACK/SILVER, 2022

obj. č: 010.22004



Sugerowana cena

7.019 zł

Aktualna cena

5.399 zł

Specyfikacje techniczne

produkowane rozmiary S: 395mm / M: 430mm / L: 470mm / XL: 520mm	rama Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle
widelec RockShox Judy Silver TK 29, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 46mm offset. Settings: Poplock 2 pos remote compression (open/lock), rebound, air preload	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings	uchwyty Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbare
mostek Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbare, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm	szttyca Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm
siodełko Mondraker XC Series, steel rail	piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
tylna piasta Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts, MS freehub	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram PG-1210, 11-50T, 12s	szprychy CN round stainless steel
rafki MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes	obudowa Maxxis Ikon 29x2.20, 60TPI, wire bead, Maxxis Ikon 29x2.20, 60TPI, wire bead
zamówienie numer 010.22004	gripy Onoff Diamond, 1lock-on, 135mm
przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba
34T, steel, X-Sync 2

mocowanie przerzutki
Mondraker M068

Galeria

