

SUMMUM CARBON RR 29 MIND, RACING SILVER/DIRTY WHITE, 2023

obj. č: 010.23185



Specyfikacje techniczne

produkowane rozmiary S / M / L / XL	rama Summum Carbon Stealth Air full Carbon, Zero Suspension System, 200mm travel, Forward Geometry, Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, HHG internal cable routing, MAX. capacity dual row Enduro bearings, shock mudguard, ISCG 05, custom frame protectors. *Geometry kit included. MIND System (EU only)
widelec Fox 40 29 Float FIT GRIP2 EVOL Factory Kashima, 203mm, air spring, 1-1/8" steerer tube, 20x110mm axle, offset 56mm. Settings: high and low-speed compression, high and low-speed rebound, air preload	stery Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm
przerzutka Shimano Saint RD-M820-SS, 10s, Shadow+, short cage	przerzutka E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider
manetki Shimano Saint SL-M820 10s, low friction multi bearing, instant release, multi release, 2-way release	klamki hamulca Shimano Saint, ergonomic antiskid lever with servo wave, free stroke and tool less reach adjust
uchwyty Shimano Saint M825 Hollowtech II, reinforced steel axle, 165mm	support Shimano 83mm
kierownica Renthal Fatbar series 7 alloy, rise: 30mm, width: 800mm, 7° backsweep, 5° upsweep, 31.8mm barbore	mostek Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer
sztyca SDG Micro I-Beam SP-951 Carbon, diameter 31.6mm, length 300mm, micro-adjustment	siodełko SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides
piasta przednia e*thirteen Boost 20x110mm, triple-sealed, fully machined aluminum, IS 6 bolts	tylna piasta e*thirteen Superboost 12x157mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts
łańcuch Shimano HG95, 10s	szprychy e*thirteen custom Hive triple-buttressed black steel, alloy nipples, nipple washers

rafki "e*thirteen LG1 Race Carbon, IW30 29"" Hookless, World Cup carbon fiber, 30mm internal width, tubeless ready, 32 spokes"	obudowa Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead
zamówienie numer 010.23185	gripy Renthal, double lock-on, kevlar compound, 130mm
amortyzator Fox DHX2 Factory Kashima, 225x70mm. Settings: high and low-speed compression, high and low-speed rebound, spring preload. Super light steel (SLS) spring. Trunnion top mount, 30x8mm bottom bushings	przedni hamulec Shimano Saint M820, 4-piston caliper, RT86 203mm 2-piece IS 6 bolts rotor with ICE technology, resin pads with cooler
tylny hamulec Shimano Saint M820, 4-piston caliper, RT86 203mm 2-piece IS 6 bolts rotor with ICE technology, resin pads with cooler	regulacja amortyzatora ECC010 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs
korba 36T, aluminum, BCD 104	

Galeria

