

# RAZE CARBON RR SL MIND, RACING SILVER/BRITISH RACING GREEN, 2023

obj. č: 010.23093

Sugerowana cena

**51.999 zł**

Aktualna cena

**38.999 zł**



## Specyfikacje techniczne

|                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>S: 380mm / M: 420mm / L: 450mm / XL: 500mm                                                                                                                                    | <b>rama</b><br>Raze 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. MIND System (EU only) |
| <b>widelec</b><br>Fox 36 29 Float GRIP2 Factory Kashima, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset.<br>Settings: high and low-speed compression, high and low-speed rebound, air preload | <b>stery</b><br>"Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"                                                                                                                                                                                                                                                             |
| <b>przerzutka</b><br>Sram XX1 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1                                                                                 | <b>manetki</b><br>Sram Eagle AXS Rocker paddle, 12s                                                                                                                                                                                                                                                                                                                        |
| <b>klamki hamulca</b><br>Sram G2 RSC, SwingLink, tool-free reach adjust                                                                                                                                      | <b>uchwyty</b><br>Sram XX1 Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm                                                                                                                                                                                                                                                              |
| <b>support</b><br>Sram DUB BSA, sealed bearings, 73mm                                                                                                                                                        | <b>kierownica</b><br>Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare                                                                                                                                                                                                                                                          |
| <b>mostek</b><br>Onoff Krypton FG 30mm, CNC, 31.8mm barbare                                                                                                                                                  | <b>sztyca</b><br>Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M size: 418.3x150mm, L/XL size: 475.1x175mm                                                                                                                                                                                                                                  |
| <b>siodełko</b><br>Fizik Antares R7                                                                                                                                                                          | <b>piasta przednia</b><br>Infinity hub, Boost 15x110mm, IS 6 bolts                                                                                                                                                                                                                                                                                                         |
| <b>tylna piasta</b><br>Infinity hub, ID360 freewheel technology, Boost 12x148mm, IS 6 bolts                                                                                                                  | <b>łańcuch</b><br>Sram GX Eagle, 12s, Powerlock                                                                                                                                                                                                                                                                                                                            |
| <b>kaseta</b><br>Sram XG-1295, 10-52T, 12s                                                                                                                                                                   | <b>szprychy</b><br>24 straight-pull double butted spokes                                                                                                                                                                                                                                                                                                                   |
| <b>rafki</b><br>Maxxis CrossMax Carbon XL R, 29 Boost 30mm internal width, hookless, tubeless ready, 24 spokes                                                                                               | <b>obudowa</b><br>Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead                                                                                                                                                  |

|                                                                                                                                                                                                                     |                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>zamówienie numer</b><br>010.23093                                                                                                                                                                                | <b>gripy</b><br>Onoff Desert, 1lock-on, 135mm                                                                                   |
| <b>amortyzator</b><br>Fox Float DPS Factory Kashima EVOL LV, 205x57.5mm. Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings | <b>przedni hamulec</b><br>Sram G2 RSC, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads |
| <b>tylny hamulec</b><br>Sram G2 RSC, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads                                                                                       | <b>regulacja amortyzatora</b><br>Light compression,light rebound, air volume spacer 0.6                                         |
| <b>korba</b><br>32T, CNC-machined alloy, X-SYNC 2                                                                                                                                                                   | <b>mocowanie przerzutki</b><br>Sram UDH                                                                                         |

Galeria

