

# CHRONO R 29, CHERRY RED/BLACK, 2022

obj. č: 010.22012



## Specyfikacje techniczne

### produkowane rozmiary

S: 395mm / M: 430mm / L: 470mm / XL: 520mm

### waga

12,5 kg

### rama

Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle

### widelec

Rockshox SID SL Base RL 29, 100mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload

### stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

### przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

### manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

### klamki hamulca

Sram Level, tooled reach adjust, lever pivot bushings

### uchwyty

Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

### support

Sram DUB BSA, sealed bearings, 73mm

### kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbore

### mostek

Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbore, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm

### sztyca

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm

### siodełko

Mondraker XC Series, steel rail

### piasta przednia

Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

### tylna piasta

Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts

### łańcuch

Sram SX Eagle, 12s, Powerlock

### kaseta

Sram PG-1210, 11-50T, 12s

### szprychy

CN round stainless steel

### rafki

MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes

### obudowa

Maxxis Ikon 29x2.20, 60TPI, wire bead, Maxxis Ikon 29x2.20, 60TPI, wire bead

### zamówienie numer

010.22012

### gripy

Onoff Diamond, 1lock-on, 135mm

### przedni hamulec

Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

**tylny hamulec**

Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

**korba**

34T, steel, X-Sync 2

**mocowanie przerzutki**

Mondraker M068

**Galeria**