

CHRONO 29 (SPE), DIRTY WHITE/BLACK, 2022

obj. č: 010.22008SPE



Specyfikacje techniczne	
produkowane rozmiary S: 395mm / M: 430mm / L: 470mm / XL: 520mm	waga 12,9 Kg
rama Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle	widelec X-Fusion RC32 29, 100mm, air spring, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 51mm. Settings: 2 pos remote compression (open/lock), rebound, air preload, X-Fusion RC
stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings
uchwyty Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbore	mostek Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbore, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm
sztyca Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm	siodełko Mondraker XC Series, steel rail
piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts	tylna piasta Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts, MS freehub
łańcuch Sram SX Eagle, 12s, Powerlock	kaseta Sram PG-1210, 11-50T, 12s
szprychy CN round stainless steel	rafki MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes
obudowa Maxxis Ikon 29x2.20, 60TPI, wire bead	zamówienie numer 010.22008SPE
gripy Onoff Diamond, 1lock-on, 135mm	przedni hamulec Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba

34T, steel, X-Sync 2

mocowanie przerzutki

Mondraker M068

Galeria