

FOXY CARBON R, BLUE/WHITE/ORANGE, 2021

obj. č: 010.21081



Sugerowana cena

27.039 zł

Aktualna cena


17.999 zł

Specyfikacje techniczne

produkowane rozmiary S 380mm / M 420mm / L 470mm / XL 510mm	waga 14,5 Kg
rama Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. Optional Geometry kit: steering cups: +/- 1	widelec Fox 36 29 Float FIT GRIP EVOL Performance, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
stery Onoff Titan tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41.8x30.5x8x45x45, bottom 51.9x40x8x45x45	przerzutka Sram Trigger NX Eagle, 12s, X-Actuation 1:1
manetki Sram Trigger NX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram G2 R, tool-free reach adjust
uchwyty Sram NX Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9 backsweep, 5 upsweep, 31.8mm barbore Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL	mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore
szttyca Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm	siodełko SDG BEL-AIR 3.0, LPU foam, steel rails
piasta przednia DT 370, Boost 15x110mm, IS 6 bolts	tylna piasta DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts
łańcuch Sram NX Eagle, 12s, Powerlock	kaseta Sram XG-1230, 11-50T, 12s
szprychy DT Champion, straightpull	rafki DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes
obudowa Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	zamówienie numer 010.21081
amortyzator Fox Float DPX2 LV EVOL Performance, 205x62.5mm. Settings: compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

tylny hamulec Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads	owijka Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
regulacja amortyzatora Light compression, extralight rebound, air volume spacer 0.6	korba 32T, steel, X-Sync 2
mocowanie przerzutki Mondraker M068	

Geometria



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	380 mm	420 mm	470 mm	510 mm
B Top Tube Length	606 mm	629 mm	654 mm	678 mm
C Bottom Bracket Drop	-21 mm	-21 mm	-21 mm	-21 mm
D Bottom Bracket Height	352 mm	352 mm	352 mm	352 mm
E Chainstay Legth	435 mm	435 mm	435 mm	435 mm
F Seat Tube Angle, Actual	70.5°	70.5°	70.5°	70.5°
G Seat Tube Angle, Effective	75.5°	75.5°	75.5°	75.5°
H Head Tube Angle	66°	66°	66°	66°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1187 mm	1210 mm	1236 mm	1262 mm
K Head Tube Length	90 mm	100 mm	115 mm	130 mm
L Reach	450 mm	470 mm	490 mm	510 mm
M Stack	605 mm	614 mm	628 mm	642 mm