

FOXY CARBON R 29 MIND, CHERRY RED/CARBON, 2022

obj. č: 010.22316



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 500mm	waga 14,1 Kg
rama Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry Kit	widelec Fox 36 29 Float FIT GRIP EVOL Rhythm, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload
stery Acros custom for 1-1/2	przerzutka Sram Trigger NX Eagle, 12s, X-Actuation 1:1
manetki Sram Trigger NX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram G2 R, tool-free reach adjust
uchwyty Truvativ Descendant 6K Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm	siodełko SDG BEL-AIR 3.0, LPU foam, steel rails
piasta przednia DT 370, Boost 15x110mm, IS 6 bolts	tylna piasta DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts
łańcuch Sram NX Eagle, 12s, Powerlock	kaseta Sram XG-1230, 11-50T, 12s
szprychy DT Champion, straightpull	rafki DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes
obudowa Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	zamówienie numer 010.22316

gripy
Onoff Diamond, 1lock-on, 135mm

przedni hamulec
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

regulacja amortyzatora
Light compression, light rebound, air volume spacer 0.6

mocowanie przerzutki
Sram UDH

amortyzator
Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

tylny hamulec
Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

korba
32T, steel, X-Sync 2

inne
*Optional Geometry kit: steering cups: +/- 1°

Galeria

