

SUMMUM 29 (SPE), DIRTY WHITE/DEEP PURPLE/FLAME RED, 2022

obj. č: 010.22080SPE



Sugerowana cena

22.359 zł

Aktualna cena

15.599 zł

Specyfikacje techniczne

produkowane rozmiary

S / M / L / XL 29

waga

17,9 kg

rama

Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual raw Enduro bearings, HHG internal cable routing, ISCG 05. *Optional Geometry kit

widelec

Fox 40 29 Float FIT GRIP EVOL Performance, 203mm, air spring, 1-1/8" steerer tube, 20x110mm axle, offset 56mm. Settings: low-speed compression, low-speed rebound, air preload

stery

Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm

przerzutka

Sram GX DH, 7s, medium cage, X-actuation 1:1

manetki

Sram trigger GX DH 7s, X-actuation 1:1

klamki hamulca

Sram G2 R, tool-free reach adjust

uchwyty

Race Face Chester, alloy, 165mm

support

Race Face BSA, 83mm

kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

mostek

Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer

szttyca

SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment

siodełko

SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

piasta przednia

MDK DA4371B-M20, Boost 20x110mm, IS 6 bolts

tylna piasta

MDK DA4352B, 12x157mm, sealed bearings, IS 6 bolts

łańcuch

Sram PC1110 11s, Powerlock

kaseta

Sram PG 720 11-25T, 7s

szprychy

CN stainless steel

rafki

MDK-DP1 29, 27mm internal width, 32 holes

obudowa

Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

zamówienie numer

010.22080SPE

gripy

Onoff Diamond, 1lock-on, 135mm

amortyzator

Fox Van RC Performance, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings

przedni hamulec Sram G2 R, 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed organic pads	tylny hamulec Sram G2 R, 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed organic pads
regulacja amortyzatora Light compression, light rebound. Spring rate: S size 400 lbs, M size 400 lbs, L size 450 lbs, XL size 500 lbs	korba 36T, E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider
mocowanie przerzutki Mondraker M068	inne *Optional geometry kit: +-1° / +-2° headset cups

Galeria

