

# F-PODIUM CARBON (SPE), CARBON/DIRTY WHITE, 2022

obj. č: 010.22044SPE



## Specyfikacje techniczne

### produkowane rozmiary

S: 390mm / M: 420mm / L: 470mm / XL: 510mm

### waga

11,5 Kg

### rama

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

### widelec

Fox 34 Step Cast Float Grip Evol Performance, 110mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, rebound, air preload, fox dual pull

### stery

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

### przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

### manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

### klamki hamulca

Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

### uchwyty

Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

### support

Sram DUB BSA, sealed bearings, 73mm

### kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare

### mostek

MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

### sztyca

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm

### siodełko

Fizik Antares R7

### piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

### tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

### łańcuch

Sram SX Eagle, 12s, Powerlock

### kaseta

Sram PG-1230, 11-50T, 12s

### szprychy

Mavic straightpull double butted, contactless lacing

### rafki

Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes

### obudowa

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

### zamówienie numer

010.22044SPE

### gripy

Onoff Diamond, 1lock-on, 135mm

### amortyzator

Fox Float DPS SV Performance Elite, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

|                                                                                                                                 |                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>przedni hamulec</b><br>Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad | <b>tylny hamulec</b><br>Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad |
| <b>regulacja amortyzatora</b><br>Firm compression, light rebound, air volume spacer 0.2                                         | <b>mocowanie przerzutki</b><br>Sram UDH                                                                                       |

Galeria

