FOXY CARBON RR 29 MIND, MARLIN BLUE/CARBON, 2022

obj. č: 010.22320



Sugerowana cena

36.399 zł

Aktualna cena

23.799 zł

Specyfikacje techniczne

produkowane rozmiary
S: 380mm / M: 420mm / L: 450mm / XL: 500mm

waga
13,4 Kg

rama
Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry Kit

widelec
Öhlins RXF 36 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

stery
Acros custom for 1-1/2

przerzutka
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki
Sram Trigger GX Eagle, 12s, X-Actuation 1:1

klamki hamulca
Sram G2 RS, SwingLink, tool-free reach adjust

uchwyty
Sram GX Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

support
Sram DUB BSA, sealed bearings, 73mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

mostek
Onoff Sulfur FG 30mm, 6061 forged alloy, 31.8mm barbore

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko
SDG BEL-AIR 3.0, LPU foam, steel rails

piasta przednia
DT 350, Boost 15x110mm, IS 6 bolts

tylna piasta
DT 350, Boost 12x148mm, 36T SL Ratchet system, IS 6 bolts, XD freehub

łańcuch
Sram NX Eagle, 12s, Powerlock

kaseta
Sram XG-1275, 10-52T, 12s

szprychy
DT Competition, straightpull

obudowa
Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

zamówienie numer
010.22320

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator
Öhlins TTX Air 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

przedni hamulec
Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

tylny hamulec
Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

regulacja amortyzatora
C20 compression, R35 rebound

korba
32T, CNC-machined alloy, X-SYNC 2

mocowanie przerzutki
Sram UDH

inne
*Optional Geometry kit: steering cups: +/- 1º

Galeria



