

# F-PODIUM DC CARBON R, GREEN/CARBON/YELLOW, 2021

obj. č: 010.21053



## Specyfikacje techniczne

### produkowane rozmiary

S 390mm / M 420mm / L 470mm / XL 510mm

### waga

11,7 Kg

### rama

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

### widelec

Fox 34 29 Float FIT4 EVOL Step Cast Factory Kashima, 120mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote lockout, compression micro-adjustment at low-speed, rebound, air preload

### stery

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

### przerzutka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

### manetki

Sram Trigger GX Eagle, 12s, X-Actuation 1:1

### klamki hamulca

Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

### uchwyty

Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm

### support

Sram DUB BSA, sealed bearings, 73mm

### kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9 backsweep, 0 upsweep, 31.8mm barbare Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL

### mostek

MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

### sztyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M/L/XL size 387x125mm

### siodełko

Fizik Antares R7

### piasta przednia

DT 370, Boost 15x110mm, IS 6 bolts

### tylna piasta

DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts, MS freehub

### łańcuch

Sram GX Eagle, 12s, Powerlock

### kaseta

Sram XG-1275, 10-50T, 12s

### szprychy

DT Champion, straightpull

### rafki

DT Swiss XRC1750 Carbon Spline 29, 30mm internal width, hookless, tubeless ready, 28 spokes

### obudowa

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

### zamówienie numer

010.21053

### amortyzator

Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunion top mount, 22.2x10mm bottom bushings

### przedni hamulec

Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

**tylny hamulec**

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

**owijka**

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

**regulacja amortyzatora**


Firm compression, light rebound, air volume spacer 0.2

**korba**

34T, CNC-machined alloy, X-SYNC 2

**mocowanie przerzutki**

Sram UDH

**Geometria****GEOMETRY**

Size	S	M	L	XL
<b>A</b> Seat Tube Length	390 mm	420 mm	470 mm	510 mm
<b>B</b> Top Tube Length	583 mm	603 mm	629 mm	654 mm
<b>C</b> Bottom Bracket Drop	-31 mm	-31 mm	-31 mm	-31 mm
<b>D</b> Bottom Bracket Height	337 mm	337 mm	337 mm	337 mm
<b>E</b> Chainstay Legth	432 mm	432 mm	432 mm	432 mm
<b>F</b> Seat Tube Angle, Actual	70.8°	70.8°	70.8°	70.8°
<b>G</b> Seat Tube Angle, Effective	75.1°	75.1°	75.1°	75.1°
<b>H</b> Head Tube Angle	66.8°	66.8°	66.8°	66.8°
<b>I</b> Fork Offset	44 mm	44 mm	44 mm	44 mm
<b>J</b> Wheelbase	1146 mm	1167 mm	1191 mm	1217 mm
<b>K</b> Head Tube Length	85 mm	90 mm	100 mm	115 mm
<b>L</b> Reach	430 mm	450 mm	470 mm	490 mm
<b>M</b> Stack	577mm	582mm	591 mm	605mm