

SUMMUM MX, DIRTY WHITE/DEEP PURPLE/FLAME RED, 2022

obj. č: 010.22084



Specyfikacje techniczne

produkowane rozmiary
S / M / L / XL 29

waga
17,9 kg

rama
Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual raw Enduro bearings, HHG internal cable routing, ISCG 05. *Optional Geometry kit

widelec
Rockshox Boxxer Select RC 29, 200mm, DebonAir, 1-1/8" steerer tube, Boost 20x110mm axle, offset 56mm.
Settings: low-speed compression, rebound, air preload

stery
Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm

przerzutka
Sram X7, 9s, short cage, X-actuation 1:1

manetki
Sram trigger X5, 9s, X-actuation 1:1

klamki hamulca
Sram Code R, tool-free reach adjust

uchwyty
Race Face Chester, alloy, 165mm

support
Race Face BSA, 83mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

mostek
Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbare, 6061 alloy, 2x6mm spacer

sztyca
SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment

siodełko
SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

piasta przednia
MDK DA4371B-M20, Boost 20x110mm, IS 6 bolts

tylna piasta
MDK DA4352B, 12x157mm, sealed bearings, IS 6 bolts

łańcuch
Sram PC-951, 9s

kaseta
Sram PG-950, 11-26T, 9s

szprychy
CN stainless steel

rafki
MDK-DP1 29, 27mm internal width, 32 holes

obudowa
Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead,

zamówienie numer
010.22084

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator
Fox Van RC Performance, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload.
Trunnion top mount, 30x8mm bottom bushings

przedni hamulec Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	tylny hamulec Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
regulacja amortyzatora Light compression, light rebound. Spring rate: S size 400 lbs, M size 400 lbs, L size 450 lbs, XL size 500 lbs	korba 36T, E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider
mocowanie przerzutki Mondraker M068	inne *Optional geometry kit: +-1° / +-2° headset cups

Galeria

