

F-PODIUM CARBON DC, NIMBUS GREY/CARBON/FLAME RED, 2023

obj. č: 010.23061



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rama F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.
widelec Rockshox SID SL Base RL 29, 120mm, DebonAir, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload, RockShox OneLoc	stery Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom
przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings	uchwyty Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare
mostek MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm	sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
siodełko Fizik Antares R7	piasta przednia Mavic, Boost 15x110mm, IS 6 bolts
tylna piasta Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram XG-1230, 11-50T, 12s	szprychy Mavic straight-pull double butted, contactless lacing
rafki Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes	obudowa Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead
zamówienie numer 010.23061	gripy Onoff Twin, 1lock-on, 135mm

amortyzator Rockshox SID Select+ RLR DebonAir, 185x50mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	regulacja amortyzatora Light compression, medium rebound, Lockout 430, 1 Token
korba 34T, steel, X-Sync 2	mocowanie przerzutki Sram UDH

Galeria

