

F-PODIUM CARBON DC, NIMBUS GREY/CARBON/FLAME RED, 2023

obj. č.: 010.23061

Sugerowana cena

26.999 zł

Aktualna cena

19.999 zł



Specyfikacje techniczne

produkowane rozmiary

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

rama

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

widelec

Rockshox SID SL Base RL 29, 120mm, DebonAir, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload, RockShox OneLoc

stery

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty

Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore

mostek

MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

szttyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm

siodełko

Fizik Antares R7

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram XG-1230, 11-50T, 12s

szprychy

Mavic straight-pull double butted, contactless lacing

rafki

Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes

obudowa

Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead

zamówienie numer

010.23061

gripy

Onoff Twin, 1lock-on, 135mm

amortyzator Rockshox SID Select+ RLR DebonAir, 185x50mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload. Trunion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	regulacja amortyzatora Light compression, medium rebound, Lockout 430, 1 Token
korba 34T, steel, X-Sync 2	mocowanie przerzutki Sram UDH

Galeria

