

PLAY 24, RACING SILVER/BLUE MARLIN, 2023

obj. č: 010.23208



Specyfikacje techniczne	
produkowane rozmiary One size: 320mm	rama Play 24 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
widelec RockShox Judy Silver TK 26, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 40mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	przerzutka Sram NX, 11s, long cage, X-actuation 1:1
manetki Sram trigger NX 11s, X-actuation 1:1	klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings
uchwyty Samox DM 28T steel, 127mm	support BSA, 73mm
kierownica MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9° backsweep, 5° upsweep, 31.8mm barbare	mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
sztyca MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 300mm	siodełko SDG Fly JR
piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts	tylna piasta Mahle-Ebikemotion X-35
łańcuch Sram PC1110 11s, Powerlock	kaseta Sram PG 1030 11-42T, 11s
szprychy CN round stainless steel	rafki MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes
obudowa Kenda Booster 24x2.4 single compound 30TPI, wire bead	zamówienie numer 010.23208
gripy Onoff Twin, 1lock-on	przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	korba 28T, steel
mocowanie przerzutki Mondraker M073	silnik + akumulator Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion

Galeria

