

PODIUM CARBON R 29, TRANSLUCENT BLUE CARBON/MARLIN BLUE, 2022

obj. č. 010.22036



Sugerowana cena

29.639 zł

Aktualna cena

19.999 zł

Specyfikacje techniczne

produkowane rozmiary S: 390mm / M: 420mm / L: 470mm / XL: 510mm	rama Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,
widelec Fox 32 Step Cast Float FIT4 EVOL Factory Kashima, 100mm, tapered steerer tube, 15x110mm Boost axle, remote lockout, offset 44mm. Settings: lockout, compression micro-adjustment at low-speed, rebound, air preload	stery Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:2	manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:2
klamki hamulca Sram Level TLM, Direct Link actuation, tooled reach adjust, lever pivot bushings	uchwyty Truvativ Stylo Carbon Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm bar bore
mostek MDK, 6061 T6 Alloy, 31.8mm bar bore, rise: +/-5°, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm	szttyca Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm
siodełko Fizik Antares R7	piasta przednia Mavic, Boost 15x110mm, IS 6 bolts
tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram XG-1275, 10-50T, 12s	szprychy Mavic straightpull double butted, contactless lacing
rafki Mavic Crossmax Carbon SL R 29, 26mm internal width, hookless, tubeless ready, 24 spokes	obudowa Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead
zamówienie numer 010.22036	gripy Onoff Diamond, 1 lock-on, 135mm

przedni hamulec Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
korba 34T, steel, X-Sync 2	mocowanie przerzutki Sram UDH

Galeria

