F-PODIUM CARBON DC, CARBON/CHERRY RED, 2022

obj. č: 010.22052



Specyfikacje techniczne

produkowane rozmiary
S: 390mm / M: 420mm / L: 470mm / XL: 510mm

waga
12,4 Kg

rama
F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

widelec
Rockshox SID Select RL 29, 120mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload

stery
Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

przerzutka
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki
Sram Trigger SX Eagle, 12s, X-Actuation 1:1

klamki hamulca
Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty
Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support
Sram DUB BSA, sealed bearings, 73mm

kierownica
Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9º backsweep, 0º upsweep, 31.8mm barbore

mostek
MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5º, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M/L/XL size 387x125mm

siodełko
Fizik Antares R7

piasta przednia
Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta
Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

łańcuch
Sram SX Eagle, 12s, Powerlock

kaseta
Sram XG-1230, 11-50T, 12s

szprychy
Mavic straightpull duble butted, contactless lacing

rafki
Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes

obudowa
Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead

zamówienie numer
010.22052

gripy
Onoff Twin, 1lock-on, 135mm

amortyzator
Rockshox SID Select+ RLR Debonair, 185x50mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

przedni hamulec
Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec
Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

regulacja amortyzatora
Light compression, medium rebound, Lockout 430, 1 Token

korba
34T, steel, X-Sync 2

mocowanie przerzutki
Sram UDH

Galeria



