LEVEL R, YELLOW/BLUE, 2021

obj. č: 010.21271



Sugerowana cena

35.359 zł

Specyfikacje techniczne

produkowane rozmiary
S 380mm / M 420mm / L 450mm / XL 490mm

waga
25,8 Kg

rama
Level 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 170mm travel, Forward Geometry, internal removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers

widelec
Fox 38 29 Float FIT GRIP EVOL Performance, 180mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

stery
Onoff Saturn tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41x30.2x7x45x4, bottom 51.9x40x8x45x45

przerzutka
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki
Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca
Sram Code R, tool-free reach adjust

uchwyty
Race Face Aeffect, 165mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9º backsweep, 5 upsweep, 31.8mm barbore,Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL

mostek
Onoff Sulfur FG 30mm 0, 6061 forged alloy, 31.8mm barbore

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko
SDG BEL-AIR 3.0, EVA foam, steel rails

piasta przednia
DT 370, Boost 15x110mm, IS 6 bolts

tylna piasta
DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts

łańcuch
Sram SX Eagle, 12s, Powerlock

kaseta
Sram PG-1210, 11-50T, 12s

szprychy
DT Hybrid SP, straightpull

rafki
DT Swiss H1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes

zamówienie numer
010.21271

amortyzator
Fox DHX2 Performance Elite, 225x75mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 25x10mm bottom bushings

przedni hamulec
Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

tylny hamulec
Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

owijka
Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead


regulacja amortyzatora
Medium compression, medium rebound. Spring rate: S/M size 300 lbs, L size 350 lbs, XL size 400 lbs

korba
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki
Mondraker M068

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4, computer Bosch Kiox, Bosch Powertube 625Wh

Geometria



GEOMETRY

Size		S	M	L	XL
A	Seat Tube Length	380 mm	420 mm	450 mm	490 mm
B	Top Tube Length	602 mm	622 mm	647 mm	667 mm
C	Bottom Bracket Drop	-15	-15	-15	-15
D	Bottom Bracket Height	357 mm	357 mm	357 mm	357 mm
E	Chainstay Legth	455 mm	455 mm	455 mm	455 mm
F	Seat Tube Angle, Actual	73.5°	73.5°	73.5°	73.5°
G	Seat Tube Angle, Effective	76.5°	76.5°	76.5°	76.5°
H	Head Tube Angle	65°	65°	65°	65°
I	Fork Offset	44 mm	44 mm	44 mm	44 mm
J	Wheelbase	1250 mm	1270 mm	1290 mm	1310 mm
K	Head Tube Length	110mm	110mm	130mm	130 mm
L	Reach	450 mm	470 mm	490 mm	510 mm
M	Stack	632 mm	632 mm	652 mm	652 mm