

FOXY R 29, DEEP PURPLE/FLAME RED, 2022

obj. č: 010.22068



Sugerowana cena

24.959 zł

Aktualna cena

16.999 zł

Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rama Foxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 150mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05
widelec Öhlins RXF 36 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram NX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram G2 R, SwingLink, tool-free reach adjust	uchwyty Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	szttyca Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm
siodełko SDG BEL-AIR 3.0, LPU foam, steel rails	piasta przednia DT 370, Boost 15x110mm, IS 6 bolts
tylna piasta DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts,	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram XG-1230, 11-50T, 12s	szprychy DT Champion, straightpull
rafki DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes	obudowa Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
zamówienie numer 010.22068	gripy Onoff Diamond, 1lock-on, 135mm

amortyzator Öhlins TTX Air 205x62.5mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
tylny hamulec Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads	regulacja amortyzatora C20 compression, R35 rebound
korba 32T, CNC-machined alloy, X-SYNC 2	mocowanie przerzutki Mondraker M068

Galeria

