# FOXY R 29, DEEP PURPLE/FLAME RED, 2022

*obj. č: 010.22068*




Sugerowana cena
**24.959 zł**
Aktualna cena
**16.999 zł**

## Specyfikacje techniczne

**produkowane rozmiary**
S: 380mm / M: 420mm / L: 470mm / XL: 510mm

**rama**
Foxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 150mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05

**widelec**
Öhlins RXF 36 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

**stery**
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

**przerzutka**
Sram NX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

**manetki**
Sram Trigger SX Eagle, 12s, X-Actuation 1:1

**klamki hamulca**
Sram G2 R, SwingLink, tool-free reach adjust

**uchwyty**
Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm

**support**
Sram DUB BSA, sealed bearings, 73mm

**kierownica**
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

**mostek**
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

**sztyca**
Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm

**siodełko**
SDG BEL-AIR 3.0, LPU foam, steel rails

**piasta przednia**
DT 370, Boost 15x110mm, IS 6 bolts

**tylna piasta**
DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts,

**łańcuch**
Sram SX Eagle, 12s, Powerlock

**kaseta**
Sram XG-1230, 11-50T, 12s

**szprychy**
DT Champion, straightpull

**rafki**
DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes

**obudowa**
Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

**zamówienie numer**
010.22068

**gripy**
Onoff Diamond, 1lock-on, 135mm

| | |
|---|---|
| **amortyzator**<br>Öhlins TTX Air 205x62.5mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings | **przedni hamulec**<br>Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads |
| **tylny hamulec**<br>Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads | **regulacja amortyzatora**<br>C20 compression, R35 rebound |
| **korba**<br>32T, CNC-machined alloy, X-SYNC 2 | **mocowanie przerzutki**<br>Mondraker M068 |

## Galeria



