

CRAFTY CARBON RR MIND, CARBON/CHERRY RED, 2022

obj. č: 010.22244



Sugerowana cena

54.599 zł

Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 490mm	rama Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
widelec Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload	stery "Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"
przerzutka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
klamki hamulca Sram G2 RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust	uchwyty Race Face Aeffect ebike, 165mm
kierownica Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	mostek Onoff Krypton FG 30mm, CNC, 31.8mm barbare
sztyca Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm	siodełko FIZIK Terra Aidon X5 145mm
piasta przednia Mavic, Boost 15x110mm, IS 6 bolts	tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
łańcuch Sram NX Eagle, 12s, Powerlock	kaseta Sram XG-1275, 10-52T, 12s
szprychy Mavic straightpull duble butted, contactless lacing	rafki Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes
obudowa Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead,	zamówienie numer 010.22244
gripy Onoff Diamond, 1lock-on, 135mm	amortyzator Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

przedni hamulec Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	tylny hamulec Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
regulacja amortyzatora medium compression, medium rebound, air volume spacer 0.2	korba Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
mocowanie przerzutki Mondraker M068	silnik + akumulator Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300

Galeria

