

# CRAFTY CARBON RR MIND, CARBON/CHERRY RED, 2022

obj. č: 010.22244



Sugerowana cena

**54.599 zł**

## Specyfikacje techniczne

|                                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>S: 380mm / M: 420mm / L: 450mm / XL: 490mm                                                                                                                                                                  | <b>rama</b><br>Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers. |
| <b>widelec</b><br>Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload | <b>stery</b><br>"Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"                                                                                                                                                                                                                                                                       |
| <b>przerzutka</b><br>Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                                                       | <b>manetki</b><br>Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click                                                                                                                                                                                                                                                                                                          |
| <b>klamki hamulca</b><br>Sram G2 RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust                                                                                                                        | <b>uchwyty</b><br>Race Face Aeffect ebike, 165mm                                                                                                                                                                                                                                                                                                                                     |
| <b>kierownica</b><br>Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare                                                                                                                          | <b>mostek</b><br>Onoff Krypton FG 30mm, CNC, 31.8mm barbare                                                                                                                                                                                                                                                                                                                          |
| <b>sztyca</b><br>Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm                                                                                                  | <b>siodełko</b><br>FIZIK Terra Aidon X5 145mm                                                                                                                                                                                                                                                                                                                                        |
| <b>piasta przednia</b><br>Mavic, Boost 15x110mm, IS 6 bolts                                                                                                                                                                                | <b>tylna piasta</b><br>Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub                                                                                                                                                                                                                                                                                           |
| <b>łańcuch</b><br>Sram NX Eagle, 12s, Powerlock                                                                                                                                                                                            | <b>kaseta</b><br>Sram XG-1275, 10-52T, 12s                                                                                                                                                                                                                                                                                                                                           |
| <b>szprychy</b><br>Mavic straightpull duble butted, contactless lacing                                                                                                                                                                     | <b>rafki</b><br>Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes                                                                                                                                                                                                                                                                                    |
| <b>obudowa</b><br>Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead,                                                                                                                          | <b>zamówienie numer</b><br>010.22244                                                                                                                                                                                                                                                                                                                                                 |
| <b>gripy</b><br>Onoff Diamond, 1lock-on, 135mm                                                                                                                                                                                             | <b>amortyzator</b><br>Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings                                                                                                                                                                          |

|                                                                                                                                 |                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>przedni hamulec</b><br>Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads | <b>tylny hamulec</b><br>Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads |
| <b>regulacja amortyzatora</b><br>medium compression, medium rebound, air volume spacer 0.2                                      | <b>korba</b><br>Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD                                                          |
| <b>mocowanie przerzutki</b><br>Mondraker M068                                                                                   | <b>silnik + akumulator</b><br>Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300       |

Galeria

