

# CHASER 750, CHERRY RED/BLACK, 2022

obj. č: 010.22300



## Specyfikacje techniczne

### produkowane rozmiary

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

### waga

24,8 Kg

### rama

Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard

### widelec

Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

### stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

### przerzutka

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

### manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

### klamki hamulca

Sram G2 R, tool-free reach adjust

### uchwyty

Race Face Aeffect ebike, 165mm

### kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

### mostek

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

### sztyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

### siodełko

FIZIK Terra Aidon X5 145mm

### piasta przednia

Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

### tylna piasta

Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

### łańcuch

Sram SX Eagle, 12s, Powerlock

### kaseta

Sram PG-1210, 11-50T, 12s

### szprychy

CN round stainless steel

### rafki

MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

### obudowa

Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

### zamówienie numer

010.22300

### gripy

Onoff Diamond, 1lock-on, 135mm

### amortyzator

RockShox Deluxe Select R Debonair, 205x65mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

### przedni hamulec

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**tylny hamulec**

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**korba**

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

---

**mocowanie przerzutki**

Mondraker M068

**silnik + akumulator**

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

---