

CHASER 750, CHERRY RED/BLACK, 2022

obj. č: 010.22300

Sugerowana cena

31.199 zł



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 490mm	waga 24,8 Kg
rama Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard	widelec Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload
stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click	klamki hamulca Sram G2 R, tool-free reach adjust
uchwyty Race Face Aeffect ebike, 165mm	kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
siodełko FIZIK Terra Aidon X5 145mm	piasta przednia Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
tylna piasta Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram PG-1210, 11-50T, 12s	szprychy CN round stainless steel
rafki MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes	obudowa Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
zamówienie numer 010.22300	gripy Onoff Diamond, 1lock-on, 135mm
amortyzator RockShox Deluxe Select R Debonair, 205x65mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings	przedni hamulec Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
tylny hamulec Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	korba Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki
Mondraker M068

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3,
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 ,
Bosch Powertube 750Wh,Bosch Kiox 300
