

F-PODIUM CARBON, CARBON/DIRTY WHITE, 2022

obj. č: 010.22044



Sugerowana cena

25.479 zł

Specyfikacje techniczne

produkowane rozmiary

S: 390mm / M: 420mm / L: 470mm / XL: 510mm

waga

11,5 Kg

rama

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

widelec

Fox 34 Step Cast Float Grip Evol Performance, 110mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, rebound, air preload

stery

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty

Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore

mostek

MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sztyca

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm

siodełko

Fizik Antares R7

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram PG-1230, 11-50T, 12s

szprychy

Mavic straightpull double butted, contactless lacing

rafki

Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes

obudowa

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

zamówienie numer

010.22044

gripy

Onoff Diamond, 1lock-on, 135mm

amortyzator

Fox Float DPS SV Performance Elite, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

przedni hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
regulacja amortyzatora Firm compression, light rebound, air volume spacer 0.2	korba 34T, steel, X-Sync 2
mocowanie przerzutki Sram UDH	

Galeria

