

# CHASER R, MARLIN BLUE/BLACK, 2022

obj. č: 010.22170



## Specyfikacje techniczne

### produkowane rozmiary

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

### waga

24,6kg

### rama

Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard

### widelec

Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

### stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

### przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

### manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

### klamki hamulca

Sram G2 R, tool-free reach adjust

### uchwyty

Race Face Aeffect ebike, 165mm

### kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

### mostek

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

### sztyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

### siodełko

FIZIK Terra Aidon X5 145mm

### piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

### tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

### łańcuch

Sram SX Eagle, 12s, Powerlock

### kaseta

Sram PG-1210, 11-50T, 12s

### szprychy

Mavic J-bend duple butted, contactless lacing

### rafki

Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

### obudowa

Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

### zamówienie numer

010.22170

### gripy

Onoff Diamond, 1lock-on, 135mm

### amortyzator

Fox Float DPS Performance, 205x65mm. Settings: Compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

### przedni hamulec

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

|                                                                                                                             |                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| <b>tylny hamulec</b><br>Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads | <b>regulacja amortyzatora</b><br>Light compression, Light rebound, 1 Token |
| <b>korba</b><br>Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD                                                        | <b>mocowanie przerzutki</b><br>Mondraker M068                              |
| <b>silnik + akumulator</b><br>Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300    |                                                                            |

Galeria

