

FACTOR 24, GRAPHITE/DESERT GREY/ORANGE, 2023

obj. č: 010.23201

Sugerowana cena

10.999 zł

Aktualna cena

9.199 zł



Specyfikacje techniczne

produkowane rozmiary One size: 300mm	rama "Factor 24 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 100mm travel, one piece bolt-on upper link, QR 9mm rear axle, 73mm BSA bottom bracket, HHG internal cable routing, dedicated 1x drivetrain design. 26"" wheelset compatible"
widelec X-Fusion Velvet RL 26, 100mm, air spring, tapered steerer tube, 9x100mm axle, 32mm aluminum stanchions, 41mm offset. Settings: lockout, rebound, air preload	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings	uchwyty Sram SX Eagle, DUB axle, Direct mount chain ring, 155mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica MDK XC 1.0, 6061 alloy, rise: 25mm, width: 680mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	sztyca Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm
siodełko SDG Fly JR	piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
tylna piasta Formula DC22LW 9x135mm, cup cone ball bearings, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram PG-1230, 11-50T, 12s	szprychy CN round stainless steel
rafki MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes	obudowa Kenda Booster 24x2.4 single compound 30TPI, wire bead
zamówienie numer 010.23201	gripy Onoff Twin, 1lock-on
amortyzator X-Fusion 02PRO R, 210x47.5mm. Settings: low-speed rebound, air preload. 45x8mm top and bottom bushings	przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec

Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts
one-piece rotor, steel-backed organic pad

regulacja amortyzatora

A-Tune light compression

korba

30T, steel, X-Sync

mocowanie przerzutki

Mondraker M073

Galeria