LEVEL RR, RACING SILVER/ÖHLINS YELLOW, 2022

obj. č: 010.22216



Specyfikacje techniczne

produkowane rozmiary
S: 380mm / M: 420mm / L: 450mm / XL: 490mm

waga
25,9 kg

rama
Level 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 170mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers

widelec
Öhlins RXF 38 M.2 29, 180mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

stery
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

przerzutka
Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki
Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca
Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust

uchwyty
Race Face Aeffect ebike, 165mm

kierownica
Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

mostek
Onoff Krypton FG 30mm, CNC, 31.8mm barbore

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko
FIZIK Terra Aidon X5 145mm

piasta przednia
e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts

łańcuch
Sram GX Eagle, 12s, Powerlock

kaseta
Sram XG-1275, 10-52T, 12s

szprychy
e*thirteen custom J-bend, triple-butted alloy, alloy nipples, nipple washers

obudowa
Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead, Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead

zamówienie numer
010.22216

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator
Öhlins TTX22M 225x75mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload. Trunnion top mount, 25x10mm bottom bushings

przedni hamulec
Sram Code RSC, oversized 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

tylny hamulec
Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

regulacja amortyzatora
C10 compression, R35 rebound. Spring rate: S size 251 lbs, M size 297 lbs, L size 343 lbs, XL size 411 lbs

korba
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki
Mondraker M068

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

Galeria



