

LEVEL RR, RACING SILVER/ÖHLINS YELLOW, 2022

obj. č: 010.22216

Sugerowana cena

46.799 zł



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 490mm	waga 25,9 kg
rama Level 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 170mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers	widelec Öhlins RXF 38 M.2 29, 180mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click	klamki hamulca Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
uchwyty Race Face Aeffect ebike, 165mm	kierownica Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Krypton FG 30mm, CNC, 31.8mm barbare	sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
siodełko FIZIK Terra Aidon X5 145mm	piasta przednia e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
łańcuch Sram GX Eagle, 12s, Powerlock	kaseta Sram XG-1275, 10-52T, 12s
szprychy e*thirteen custom J-bend, triple-buttressed alloy, alloy nipples, nipple washers	obudowa Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead, Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
zamówienie numer 010.22216	gripy Onoff Diamond, 1lock-on, 135mm
amortyzator Öhlins TTX22M 225x75mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload. Trunnion top mount, 25x10mm bottom bushings	przedni hamulec Sram Code RSC, oversized 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
tylny hamulec Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	regulacja amortyzatora C10 compression, R35 rebound. Spring rate: S size 251 lbs, M size 297 lbs, L size 343 lbs, XL size 411 lbs

korba

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki

Mondraker M068

silnik + akumulator

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch
Powertube 750Wh, Bosch Kiox 300

Galeria