

RAZE, BLACK/DIRTY WHITE, 2023

obj. č: 010.23077

Sugerowana cena

17.499 zł



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rama Raze 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 130mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05
widelec RockShox 35 Gold 29 RL, 150mm, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings	uchwyty Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
siodełko MDK series PU 2023	piasta przednia Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
tylna piasta Formula DHT148 Boost 12x148mm, sealed bearings, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram PG-1210, 11-50T, 12s	szprychy CN round stainless steel
rafki MDK-EP1 29, 30mm internal width, tubeless ready, 32 spokes	obudowa Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
zamówienie numer 010.23077	gripy Onoff Twin, 1lock-on, 135mm

amortyzator Fox Float DPS LV EVOL Performance, 205x57.5mm. Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings	przedni hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	regulacja amortyzatora Light compression, light rebound, air volume spacer 0.6
korba 32T, steel, X-Sync 2	mocowanie przerzutki Sram UDH

Galeria

