

CHRONO CARBON RR 29, CARBON/BLACK/RACING SILVER, 2022

obj. č.: 010.22028



Specyfikacje techniczne

produkowane rozmiary

S: 395mm / M: 430mm / L: 470mm / XL: 520mm

rama

Chrono 29 Stealth full Carbon, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable routing, Boost 12x148mm rear axle, Comfort Flat chainstays (Flatstays) design

widelec

Rockshox SID SL Ultimate RL 29, 100mm, Charger Race day, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload

stery

Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°

przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger NX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty

Sram GX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare

mostek

MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: size S: 60mm, size M: 70mm, size L: 80mm, size XL: 90mm

sztyca

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm

siodełko

Mondraker XC Series, steel rail

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram PG-1230, 11-50T, 12s

szprychy

Mavic straightpull double butted, contactless lacing

rafki

Mavic Crossmax SL S 29, 25mm internal width, Maxtal welded rim, hookless, tubeless, 24 spokes

obudowa

Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead, Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead

zamówienie numer

010.22028

gripy

Onoff Diamond, 1lock-on, 135mm

przedni hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
korba 34T, CNC-machined alloy, X-SYNC 2	mocowanie przerzutki Mondraker M068

Galeria

