

CHRONO CARBON RR 29, CARBON/BLACK/RACING SILVER, 2022

obj. č: 010.22028



Sugerowana cena

17.419 zł

Specyfikacje techniczne

produkowane rozmiary S: 395mm / M: 430mm / L: 470mm / XL: 520mm	rama Chrono 29 Stealth full Carbon, XC Forward Geometry, 73mm BSA bottom bracket, tapered steerer tube, HHG Internal Cable routing, Boost 12x148mm rear axle, Comfort Flat chainstays (Flatstays) design
widelec Rockshox SID SL Ultimate RL 29, 100mm, Charger Race day, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload	stery Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger NX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level T, Direct Link actuation, tooling reach adjust, lever pivot bushings	uchwyty Sram GX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm bar bore
mostek MDK, 6061 T6 Alloy, 31.8mm bar bore, rise: +/-5°, length: size S: 60mm, size M: 70mm, size L: 80mm, size XL: 90mm	sztyca Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm
siodełko Mondraker XC Series, steel rail	piasta przednia Mavic, Boost 15x110mm, IS 6 bolts
tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram PG-1230, 11-50T, 12s	szprychy Mavic straightpull double butted, contactless lacing
rafki Mavic Crossmax SL S 29, 25mm internal width, Maxtal welded rim, hookless, tubeless, 24 spokes	obudowa Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead, Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead
zamówienie numer 010.22028	gripy Onoff Diamond, 1lock-on, 135mm
przedni hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba

34T, CNC-machined alloy, X-SYNC 2

mocowanie przerzutki

Mondraker M068

Galeria

