

# PRIME 29 (SPE), BLACK/RACING SILVER, 2022

obj. č: 010.22174SPE



Sugerowana cena

**21.399 zł**

## Specyfikacje techniczne

|                                                                                                                                                                                                              |                                                                                                                                                                                                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm                                                                                                                        | <b>waga</b><br>22,2 Kg                                                                                                                                                                                              |
| <b>rama</b><br>Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery with integrated alloy cover, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor | <b>widelec</b><br>RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload |
| <b>stery</b><br>Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°                                                                    | <b>przerzutka</b><br>Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1                                                                                                      |
| <b>manetki</b><br>Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click                                                                                                                                  | <b>klamki hamulca</b><br>Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings                                                                                                            |
| <b>uchwyty</b><br>Race Face Aeffect ebike, 165mm                                                                                                                                                             | <b>kierownica</b><br>Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore                                                                                 |
| <b>mostek</b><br>Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore                                                                                                                                 | <b>szttyca</b><br>Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm                                                                                                                         |
| <b>siodełko</b><br>FIZIK Terra Aidon X5 145mm                                                                                                                                                                | <b>piasta przednia</b><br>Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts                                                                                                                                |
| <b>tylna piasta</b><br>Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts                                                                                                                            | <b>łańcuch</b><br>Sram SX Eagle, 12s, Powerlock                                                                                                                                                                     |
| <b>kaseta</b><br>Sram PG-1210, 11-50T, 12s                                                                                                                                                                   | <b>szprychy</b><br>CN round stainless steel                                                                                                                                                                         |
| <b>rafki</b><br>MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes                                                                                                                                   | <b>obudowa</b><br>Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead                  |
| <b>zamówienie numer</b><br>010.22174SPE                                                                                                                                                                      | <b>gripy</b><br>Onoff Diamond, 1lock-on, 135mm                                                                                                                                                                      |
| <b>przedni hamulec</b><br>Sram Level TL, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                              | <b>tylny hamulec</b><br>Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                       |
| <b>korba</b><br>Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD                                                                                                                                         | <b>mocowanie przerzutki</b><br>Mondraker M068                                                                                                                                                                       |

### **silnik + akumulator**

Bosch Performance Line CX Cruise (25Km/h) GEN4, Bosch  
Powertube 625Wh, Bosch Purion

---

### **Galeria**

---

