

RAZE CARBON R MIND, CARBON/GLOSS BLACK/RACING SILVER, 2022

obj. č: 010.22304



Specyfikacje techniczne

produkowane rozmiary

S: 380mm / M: 420mm / L: 450mm / XL: 500mm

waga

13,2 Kg

rama

New Trail 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.

widelec

Fox 36 29 Float GRIP EVOL Performance, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

stery

Acros custom for 1-1/2

przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger NX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram G2, SwingLink, tool-free reach adjust

uchwyty

Truvativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

mostek

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

sztyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko

Fizik Antares R7

piasta przednia

DT 350, Boost 15x110mm, IS 6 bolts

tylna piasta

DT 350, Boost 12x148mm, 36T SL Ratchet system, IS 6 bolts, XD freehub

łańcuch

Sram NX Eagle, 12s, Powerlock

kaseta

Sram XG-1275, 10-52T, 12s

szprychy

DT Competition, straightpull

rafki

DT Swiss XM1700 Spline 29, 30mm internal width, welded aluminum, tubeless ready, 28 spokes

obudowa

Maxxis Aggressor 29x2.3, tubeless ready, dual compound,EXO protection, 60TPI, folding bead, Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

zamówienie numer

010.22304

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator
Fox Float DPS LV EVOL Performance, 205x57.5mm.
Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings

przedni hamulec
Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

tylny hamulec
Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

regulacja amortyzatora
Light compression, extralight rebound, air volume spacer 0.6

korba
32T, CNC-machined alloy, X-SYNC 2

mocowanie przerzutki
Sram UDH

Galeria

