

# RAZE CARBON R MIND, CARBON/GLOSS BLACK/RACING SILVER, 2022

obj. č: 010.22304



| Specyfikacje techniczne                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>S: 380mm / M: 420mm / L: 450mm / XL: 500mm                                                                                                                                                                                                                                                                                 | <b>waga</b><br>13,2 Kg                                                                                                                                                                                      |
| <b>rama</b><br>New Trail 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. | <b>widelec</b><br>Fox 36 29 Float GRIP EVOL Performance, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload |
| <b>stery</b><br>Acros custom for 1-1/2                                                                                                                                                                                                                                                                                                                    | <b>przerzutka</b><br>Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                         |
| <b>manetki</b><br>Sram Trigger NX Eagle, 12s, X-Actuation 1:1                                                                                                                                                                                                                                                                                             | <b>klamki hamulca</b><br>Sram G2, SwingLink, tool-free reach adjust                                                                                                                                         |
| <b>uchwyty</b><br>Truvativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm                                                                                                                                                                                                                                    | <b>support</b><br>Sram DUB BSA, sealed bearings, 73mm                                                                                                                                                       |
| <b>kierownica</b><br>Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore                                                                                                                                                                                                                        | <b>mostek</b><br>Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore                                                                                                                                 |
| <b>szttyca</b><br>Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm                                                                                                                                                                                                                                | <b>siodełko</b><br>Fizik Antares R7                                                                                                                                                                         |
| <b>piasta przednia</b><br>DT 350, Boost 15x110mm, IS 6 bolts                                                                                                                                                                                                                                                                                              | <b>tylna piasta</b><br>DT 350, Boost 12x148mm, 36T SL Ratchet system, IS 6 bolts, XD freehub                                                                                                                |
| <b>łańcuch</b><br>Sram NX Eagle, 12s, Powerlock                                                                                                                                                                                                                                                                                                           | <b>kaseta</b><br>Sram XG-1275, 10-52T, 12s                                                                                                                                                                  |
| <b>szprychy</b><br>DT Competition, straightpull                                                                                                                                                                                                                                                                                                           | <b>rafki</b><br>DT Swiss XM1700 Spline 29, 30mm internal width, welded aluminum, tubeless ready, 28 spokes                                                                                                  |
| <b>obudowa</b><br>Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead, Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead                                                                                                                                  | <b>zamówienie numer</b><br>010.22304                                                                                                                                                                        |

**gripy**  
Onoff Diamond, 1lock-on, 135mm

**amortyzator**  
Fox Float DPS LV EVOL Performance, 205x57.5mm.  
Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings

**przedni hamulec**  
Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

**tylny hamulec**  
Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

**regulacja amortyzatora**  
Light compression, extralight rebound, air volume spacer 0.6

**korba**  
32T, CNC-machined alloy, X-SYNC 2

**mocowanie przerzutki**  
Sram UDH

Galeria

