

CRAFTY R, BLACK/GRAPHITE, 2022

obj. č: 010.22224



Sugerowana cena

34.839 zł

Aktualna cena

25.999 zł

Specyfikacje techniczne

produkowane rozmiary

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

waga

25,1kg

rama

Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

widelec

Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca

Sram G2 R, tool-free reach adjust

uchwyty

Race Face Aeffect ebike, 165mm

kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

mostek

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

szttyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko

FIZIK Terra Aidon X5 145mm

piasta przednia

Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram PG-1210, 11-50T, 12s

szprychy

Mavic J-bend duble butted, contactless lacing

rafki

Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

obudowa

Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

zamówienie numer

010.22224

gripy

Onoff Diamond, 1lock-on, 135mm

amortyzator
Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

tylny hamulec
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

korba
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300

przedni hamulec
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

regulacja amortyzatora
medium compression, medium rebound, air volume spacer 0.2

mocowanie przerzutki
Mondraker M068

Galeria

