

CHRONO R 29, BRITISH RACING GREEN/ÖHLINS YELLOW, 2022

obj. č: 010.22016



Sugerowana cena

9.359 zł

Specyfikacje techniczne

produkowane rozmiary S: 395mm / M: 430mm / L: 470mm / XL: 520mm	waga 12,5 kg
rama Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle	widelec Rockshox SID SL Base RL 29, 100mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload
stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings
uchwyty Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbore	mostek Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbore, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm
sztyca Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm	siodełko Mondraker XC Series, steel rail
piasta przednia Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts	tylna piasta Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts
łańcuch Sram SX Eagle, 12s, Powerlock	kaseta Sram PG-1210, 11-50T, 12s
szprychy CN round stainless steel	rafki MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes
obudowa Maxxis Ikon 29x2.20, 60TPI, wire bead, Maxxis Ikon 29x2.20, 60TPI, wire bead	zamówienie numer 010.22016
gripy Onoff Diamond, 1lock-on, 135mm	przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	korba 34T, steel, X-Sync 2

mocowanie przerzutki
Mondraker M068

Galeria

