# PODIUM CARBON R, CARBON/YELLOW/GREEN, 2021

*obj. č: 010.21025*

Sugerowana cena
**25.999 zł**

## Specyfikacje techniczne

| | |
|---|---|
| **produkowane rozmiary**<br>S 390mm / M 420mm / L 470mm / XL 510mm | **waga**<br>8,9 Kg |
| **rama**<br>Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible, | **widelec**<br>Fox 32 29 Float FIT4 EVOL Step Cast Factory Kashima, 100mm, tapered steerer tube,15x110mm Boost axle, remote lockout, offset 44mm. Settings: lockout, compression micro-adjustment at low-speed, rebound, air preload |
| **stery**<br>Onoff Titan tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41.8x30.5x8x45x45, bottom 51.9x40x8x45x45 | **przerzutka**<br>Shimano XT M8100, SGS, Shadow+, 12s |
| **manetki**<br>Shimano SLX M7100, Rapid Fire Plus, 12s | **klamki hamulca**<br>Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust |
| **uchwyty**<br>Shimano XT M8100 Boost, Hollowtech II, Q-factor 172mm, S size: 170mm, M/L/XL size: 175mm | **support**<br>Shimano XT MT800 BSA, 68/73mm |
| **kierownica**<br>Onoff Helium Carbon 0.2, rise: 4.8mm, width: 740mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Twin, 1lock-on, 135mm | **mostek**<br>MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm |
| **sztyca**<br>Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm | **siodełko**<br>Fizik Antares R7 |
| **piasta przednia**<br>DT 350, Boost 15x110mm, CenterLock | **tylna piasta**<br>DT 350, Boost 12x148mm, 36T SL Ratchet system, CenterLock, MS freehub |
| **łańcuch**<br>Shimano Deore M6100, 12s, Quick-link | **kaseta**<br>Shimano SLX M7100 10-51T Hyperglide+, 12s |
| **szprychy**<br>DT Competition, straightpull | **rafki**<br>DT Swiss XR1700 Spline 29, 25mm internal width, welded aluminum, tubeless ready, 28 spokes |
| **obudowa**<br>Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead | **zamówienie numer**<br>010.21025 |
| **przedni hamulec**<br>Shimano XT M8100, MT800 ICE-Tech 160mm CenterLock rotor, resin pads | **tylny hamulec**<br>Shimano XT M8110, MT800 ICE-Tech 160mm CenterLock rotor, resin pads, Flatmount |

**owijka**
Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead

**korba**
34T, CNC-machined alloy

**mocowanie przerzutki**
Sram UDH

## Geometria




### GEOMETRY

| Size | S | M | L | XL |
|---|---|---|---|---|
| A Seat Tube Length | 390 mm | 420 mm | 470 mm | 510 mm |
| B Top Tube Length | 590 mm | 611mm | 632 mm | 650 mm |
| C Bottom Bracket Drop | -65 mm | -65 mm | -65 mm | -65 mm |
| D Bottom Bracket Height | 305 mm | 305 mm | 305 mm | 305 mm |
| E Chainstay Legth | 430 mm | 430 mm | 430 mm | 430 mm |
| F Seat Tube Angle, Actual | 73° | 73° | 73° | 73° |
| G Seat Tube Angle, Effective | 74.5° | 74.5° | 74.5° | 74.5° |
| H Head Tube Angle | 68.5° | 68.5° | 68.5° | 68.5° |
| I Fork Offset | 44 mm | 44 mm | 44 mm | 44 mm |
| J Wheelbase | 1107 mm | 1128 mm | 1150 mm | 1170 mm |
| K Head Tube Length | 85 mm | 90 mm | 100 mm | 115 mm |
| L Reach | 425 mm | 444 mm | 463 mm | 477 mm |
| M Stack | 598 mm | 602 mm | 611 mm | 625 mm |