PODIUM CARBON R, CARBON/YELLOW/GREEN, 2021

obj. č: 010.21025

Sugerowana cena
25.999 zł

Specyfikacje techniczne

produkowane rozmiary S 390mm / M 420mm / L 470mm / XL 510mm	**waga** 8,9 Kg
rama Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,	**widelec** Fox 32 29 Float FIT4 EVOL Step Cast Factory Kashima, 100mm, tapered steerer tube,15x110mm Boost axle, remote lockout, offset 44mm. Settings: lockout, compression micro-adjustment at low-speed, rebound, air preload
stery Onoff Titan tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41.8x30.5x8x45x45, bottom 51.9x40x8x45x45	**przerzutka** Shimano XT M8100, SGS, Shadow+, 12s
manetki Shimano SLX M7100, Rapid Fire Plus, 12s	**klamki hamulca** Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust
uchwyty Shimano XT M8100 Boost, Hollowtech II, Q-factor 172mm, S size: 170mm, M/L/XL size: 175mm	**support** Shimano XT MT800 BSA, 68/73mm
kierownica Onoff Helium Carbon 0.2, rise: 4.8mm, width: 740mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Twin, 1lock-on, 135mm	**mostek** MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm
sztyca Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm	**siodełko** Fizik Antares R7
piasta przednia DT 350, Boost 15x110mm, CenterLock	**tylna piasta** DT 350, Boost 12x148mm, 36T SL Ratchet system, CenterLock, MS freehub
łańcuch Shimano Deore M6100, 12s, Quick-link	**kaseta** Shimano SLX M7100 10-51T Hyperglide+, 12s
szprychy DT Competition, straightpull	**rafki** DT Swiss XR1700 Spline 29, 25mm internal width, welded aluminum, tubeless ready, 28 spokes
obudowa Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead	**zamówienie numer** 010.21025
przedni hamulec Shimano XT M8100, MT800 ICE-Tech 160mm CenterLock rotor, resin pads	**tylny hamulec** Shimano XT M8110, MT800 ICE-Tech 160mm CenterLock rotor, resin pads, Flatmount

owijka
Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead

korba
34T, CNC-machined alloy

mocowanie przerzutki
Sram UDH

Geometria



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	390 mm	420 mm	470 mm	510 mm
B Top Tube Length	590 mm	611mm	632 mm	650 mm
C Bottom Bracket Drop	-65 mm	-65 mm	-65 mm	-65 mm
D Bottom Bracket Height	305 mm	305 mm	305 mm	305 mm
E Chainstay Legth	430 mm	430 mm	430 mm	430 mm
F Seat Tube Angle, Actual	73°	73°	73°	73°
G Seat Tube Angle, Effective	74.5°	74.5°	74.5°	74.5°
H Head Tube Angle	68.5°	68.5°	68.5°	68.5°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1107 mm	1128 mm	1150 mm	1170 mm
K Head Tube Length	85 mm	90 mm	100 mm	115 mm
L Reach	425 mm	444 mm	463 mm	477 mm
M Stack	598 mm	602 mm	611 mm	625 mm