

SUMMUM R MX, BRITISH RACING GREEN/BLACK/ÖHLINS YELLOW, 2022

obj. č.: 010.22092



Sugerowana cena

30.159 zł

Specyfikacje techniczne

produkowane rozmiary S / M / L / XL 29	rama Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual raw Enduro bearings, HHG internal cable routing, ISCG 05. *Optional Geometry kit
widelec Fox 40 29 Float FIT GRIP EVOL Performance, 203mm, air spring, 1-1/8" steerer tube, 20x110mm axle, offset 56mm. Settings: low-speed compression, low-speed rebound, air preload	stery Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm
przerzutka Sram trigger GX DH 7s, X-actuation 1:1	manetki Sram trigger GX DH 7s, X-actuation 1:1
klamki hamulca Sram Code R, tool-free reach adjust	uchwyty Truvativ Descendant DH, DUB axle, Direct mount chain ring, 165mm
support Sram DUB BSA, sealed bearings, 83mm	kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbare, 6061 alloy, 2x6mm spacer	szttyca SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment
siodełko SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides	piasta przednia e*thirteen Boost 20x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
łańcuch Sram PC1110 11s, Powerlock	kaseta Sram PG 720 11-25T, 7s
szprychy e*thirteen custom Hive triple-buttet black alloy, alloy nipples, nipple washers	rafki e*thirteen LG1 Plus DH, IW29 29
obudowa Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead, Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead	zamówienie numer 010.22092
gripy Onoff Diamond, 1lock-on, 135mm	amortyzator Fox DHX2 Performance Elite, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings

przedni hamulec Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	tylny hamulec Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
regulacja amortyzatora ECC010 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs	korba 34T, steel, X-SYNC, E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider
mocowanie przerzutki Mondraker M068	inne *Optional geometry kit: +-1° / +-2° headset cups

Galeria

