

PLAY 24, BLACK/RACING SILVER/FLAME RED, 2022

obj. č: 010.22292



Sugerowana cena

12.999 zł

Specyfikacje techniczne

produkowane rozmiary One size: 320mm	rama Play 24 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
widelec RockShox Judy Silver TK 26, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 40mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram NX, 11s, long cage, X-actuation 1:1	manetki Sram trigger NX 11s, X-actuation 1:1
klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings	uchwyty Prowheel, Direct mount chain ring, 127mm
support Prowheel BSA, 73mm	kierownica MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9° backsweep, 5° upsweep, 31.8mm barbore
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sztyca MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 300mm
siodełko SDG Fly JR	piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
tylna piasta Mahle-Ebikemotion X-35	łańcuch Sram PC1110 11s, Powerlock
kaseta Sram PG 1030 11-42T, 11s	szprychy CN round stainless steel
rafki MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes	obudowa Kenda Booster 24x2.4 single compound 30TPI, wire bead, Kenda Booster 24x2.4 single compound 30TPI, wire bead
zamówienie numer 010.22292	gripy Onoff Twin, 1lock-on, 135mm
przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
korba 28T, steel	mocowanie przerzutki Mondraker M073
silnik + akumulator Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion	

Galeria

