F-PODIUM CARBON DC R, CARBON/BLACK/RACING SILVER, 2022

obj. č: 010.22056

Sugerowana cena
38.999 zł

Specyfikacje techniczne

produkowane rozmiary
S: 390mm / M: 420mm / L: 470mm / XL: 510mm

rama
F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

widelec
Rockshox SID Ultimate RL 29, 120mm, Charger Race day, Debonair, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLoc, Low-speed rebound, air preload

stery
Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

przerzutka
Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki
Sram Trigger GX Eagle, 12s, X-Actuation 1:1

klamki hamulca
Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty
Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm

support
Sram DUB BSA, sealed bearings, 73mm

kierownica
Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9º backsweep, 0º upsweep, 31.8mm barbore

mostek
MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5º, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M/L/XL size 387x125mm

siodełko
Fizik Antares R7

piasta przednia
Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta
Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

łańcuch
Sram GX Eagle, 12s, Powerlock

kaseta
Sram XG-1275, 10-50T, 12s

szprychy
Mavic straightpull duble butted, contactless lacing

rafki
Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes

obudowa
Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead

zamówienie numer
010.22056

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator Rockshox SID Luxe Ultimate RLR Debonair, 185x50mm. Settings: OneLoc, low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	**przedni hamulec** Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	**regulacja amortyzatora** Firm compression, light rebound, air volume spacer 0.2
korba 34T, CNC-machined alloy, X-SYNC 2	**mocowanie przerzutki** Sram UDH

Galeria