

PRIME R, CHERRY RED/BLACK, 2022

obj. č: 010.22142

Sugerowana cena

23.919 zł



Specyfikacje techniczne

produkowane rozmiary

XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm

widelec

RockShox 35 Silver TK 29, 120mm, TurnKey, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload

przerzutka

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

klamki hamulca

Sram G2 R, tool-free reach adjust

kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore

szttyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

piasta przednia

Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

łańcuch

Sram SX Eagle, 12s, Powerlock

szprychy

CN round stainless steel

obudowa

Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

gripy

Onoff Diamond, 1lock-on, 135mm

tylny hamulec

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

mocowanie przerzutki

Mondraker M068

rama

Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal non-removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor

stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

uchwyty

Race Face Aeffect ebike, 165mm

mostek

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

siodełko

FIZIK Terra Aidon X5 145mm

tylna piasta

Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

kaseta

Sram PG-1210, 11-50T, 12s

rafki

MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

zamówienie numer

010.22142

przedni hamulec

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

korba

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

silnik + akumulator

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS , Bosch Powertube 750Wh, Bosch Kiox 300

Galeria

